



Applications

Waterblast:

Heat exchanger tube cleaning, surface preparation (concrete removal, surface cleaning of buildings, paint removal), tank and vessel cleaning, ultra high-pressure waterjet cutting and hydro demolition (cutting and demolition of armoured concrete, pipelines, paper or steel)

Hydraulics:

Pressure test equipment (valves, tooling and control panels)



Technical Information

Inner Core: Polyoxymethylene (POM)

Pressure Support: 6 layers of high-tensile steel wire


Outer Cover: Polyamide (PA)

Colour: Blue


Temperature: -30°C to +60°C [-22°F to 140°F]

Ø ID	Ø OD	Working Pressure (SF 2.5:1)	--	Burst Pressure	Bend Radius	Weight	Insert ID
8,0 mm	16,4 mm	2.100 bar	--	5.250 bar	250 mm	0,640 kg/m	4,5 mm
0,31 inch	0,65 inch	30.450 psi	--	76.125 psi	9,84 inch	0,429 lbs/ft	0,18 inch


Part no.	Thread	Material	Dimensions (mm) A B C	⚙	Sleeve
10860106	-	Steel	21,6 64 - -		




Part no.	Thread	Material	Nut	Dimensions (mm) A B C	⚙	Insert
HP fitting						
40860214C	3/8"x24UNF LH	Stainless steel	-	4,5 100 20	-	
40860204C	9/16"x18UNF LH	Stainless steel	-	4,5 112 31	-	
40860104C	M14x1.5 LH	Stainless steel	-	4,5 112 24	-	




MP fitting						
40860324C	3/4"x16UNF LH	Stainless steel	-	4,5 102 18	-	



Female swivel with O-Ring						
20860224C	M24x1.5	Stainless steel	51320205, 51321206	4,5 91 - 32		



Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C		
Type M female swivel								
20860644C	3/4"x16UNF	Stainless steel	50840605, 50840601	4,5	76	-	24	
20860684C	7/8"x14UNF	Stainless steel	50860675	4,5	77	-	30	

Part no.	Thread	Material	Relief bores	Dimensions (mm)				Swivel nut
				A	B	C		
Swivel nut								
50840601	3/4"x16UNF	Steel	1 radial	12,2	22,5	17,5	24	
50840605	3/4"x16UNF	AISI 316Ti	1 radial	12,2	22,5	17,5	24	
50860675	7/8"x14UNF	AISI 316Ti	1 radial	12,2	26	20	30	
51321206	M24x1.5	Steel	2 axial	16,8	23	16	32	
51320205	M24x1.5	AISI 316Ti	1 radial	16,8	23	16	32	

Part no.	Size (mm)	Material	Crimp ring	Hose protection
Hose protection without spiral				
I.902228	ID Ø22, OD Ø28	PVC	I002830	
I.902531	ID Ø25, OD Ø31	PVC	-	
I.903037	ID Ø30, OD Ø39	PVC	I003941	
Hose protection with spiral				
I.912229	ID Ø22, OD Ø35	PVC	I003035	
I.913240	ID Ø32, OD Ø40	PVC	-	

Part no.	Material	Crimp ring	Dimensions (mm)		Bend restrictor
			Ø	Length	
TPU bend restrictor					
I.9523406A	PUR	I004145	44	250	

Part no.	Mesh length (mm)	Overall length (mm)	Breaking strength (kN)	Suitable for SPIR STAR® hose outer diameter (mm)	Hose securing grip
Hose securing grip short version					
9086400	600,00	780,00	20,40	15-20	
Hose securing grip long version					
908640L	600,00	990,00	20,40	15-20	

Accessories combinations				
Without hose protection				
Description		Bend restrictor	Crimp ring	Securing grips
Bend restrictor		I.9523406A	I004145	-
Securing grip		-	-	9086400
Bend restrictor and securing grip		I.9523406A	I004145	908640L
Hose protection without spiral				
Description	Protection hose	Bend restrictor	Crimp ring	Securing grips
Protection hose	I.902228	-	I002830	-
with bend restrictor	I.903037	I.9523406A	I004145	-
with securing grip	I.902531	-	-	9086400
with bend restrictor and securing grip	I.903037	I.9523406A	I004145	908640L
Hose protection with spiral				
Description	Protection hose	Bend restrictor	Crimp ring	Securing grips
Protection hose	I.912229	-	I003035	-
with bend restrictor	I.913240	I.9523406A	I004145	-
with securing grip	I.912532	-	-	9086400
with bend restrictor and securing grip	I.913240	I.9523406A	I004145	908640L

Production-related variations of the burst pressure of up to 5 % are possible. Other colours upon request.

The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked.

Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center.

The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly may be less.

*) Blast-Pro® fittings may only be used for tube cleaning operations inside the tube. They have not been designed for the use outside of tubes.

We reserve our rights for technical changes without notice. Subject to printing errors.